

Model	Approx Year of Manufacture	Moulded Length with Bow Sprit	Length (m)	Beam (m)	Deadrise	Fuel O/B (L)	Min HP	Max HP	Berths	Max Eng Weight - Kg (O/B)	Approx Hull Weight (kg)	Approx Towing Weight (kg)	Water	BMT Length (approx)	BMT Height (approx)	BMT Width (approx)	Max People	Max load (people, gear, fuel)	Boat Type	Transom Height (inch)
1500S	90-00		4.65	1.90	22.5 °	Portable	35	90		170	350						4		OPEN	20
1550BR	88-90		5.33	2.13	22.5 °	165	75	140		200	560						5		OPEN	20
1550C	86-89		4.72	2.00	22.5 °	100	40	120	2	170	420						5		CABIN	20
1550F	86-94		4.72	2.00	22.5 °	n/a	40	60	2	170	400						4		CABIN	20
1550LE	88-90		5.33	2.13	22.5 °	165	75	130	2	200	560						5		OPEN	20
1550R	86-91		4.72	2.00	22.5 °	100	40	125		170	370						5		OPEN	20
1550RE	88-90		5.33	2.13	21-29 °	165	75	140		200	610						5		CABIN	20
1700S	85-95	5.48	5.20	1.92	22.5 °	160	90	150		200	400						5		OPEN	20
1750C	85-88		5.33	2.13	22.5 °	130	100	150	2	200	600						5		CABIN	20
1750L	87-90		5.33	2.13	22.5 °	130	75	150	2	200	600						5		CABIN	20
1750LE	88-90		5.95	2.21	22.5-34 °	150	90	150	2	230	750						6		CABIN	20
1750R	85-92		5.33	2.13	22.5 °	130	100	235		200	500						5		OPEN	20
1750RE	88-90		5.95	2.21	22.5-34 °	150	90	200	-	230	700						6		RUNABOUT	20
1800S	95-02		5.48	1.92	22.5 °	160	75	150		200	470						5		OPEN	20
1850L	88-90		6.25	2.28	22.5-31 °	210	135	200	2	270	756						6		CABIN	20
1850LE	88-90		6.25	2.28	22.5-31 °	210	115	200	2	270	756		Optional 50L				6		CABIN	20
1850R	88-90		6.25	2.28	22.5-31 °	210	135	220		270	700						6		CABIN	20
1850RE	88-90		6.25	2.28	22.5-31 °	210	115	220		270	700						6		RUNABOUT	20
1900S	90-02		6.40	2.03	21-29 °	165	115	225		270	600						5		OPEN	20
1950L	86-90		6.55	2.44	22.5-31 °	210	150	235	2	270	985						6		CABIN	20
1950LE	88-90		6.55	2.44	22.5-31 °	210	135	235	2	270	985		Optional 50L				6		CABIN	20
1950R	87-90		6.55	2.44	22.5-31 °	210	150	235	2	270	950						6		CABIN	20
1950RE	88-90		6.55	2.44	22.5-31 °	210	135	235	2	270	950		Optional 50L				6		RUNABOUT	20
2100S	88-02		6.48	2.20	22.5-31 °	190	135	225		200	800						6		OPEN	20
2250L	85-90		6.90	2.50	22.5 °	245	150	235	2	270	1210						7		CABIN	20
2250SB	88-90		6.90	2.50	22.5 °	245	175	235	4	270	1130		90L				7		SPORTSBRIDGE	20
460BR	98-07	4.8	4.60	2.09	21-33 °	85	50	90		190	440						5		BOW RIDER	20
460C	90-02	4.8	4.60	2.09	21-33 °	85	50	75	2	170	450						5		CABIN	20
460DF	99-07	4.8	4.60	2.09	21-33 °	85	50	75	Day	170	450	1020					5		CABIN	20
460R	96-98	4.8	4.60	2.09	21-33 °	85	50	90		170	375						5		OPEN	20
460SF	?-10	4.80m	4.60m	2.09m	21-33 °	85	50	90		190	450	1100		5.98m	1.78m	2.09m	5	500kg	OPEN	20
470DF	94-00		4.72	2.00	22.5 °	0	40	75	Day	170	400						5		CABIN	20
470F	94-00		4.72	2.00	22.5 °	0	40	60	2	170	380						5		CABIN	20
470R			4.80	2.00	22.5 °		40										5			
490F	91-92		4.87	2.01	22.5 °	100	60	90	2	170	420						5		CABIN	20
490L	91-92		4.87	2.01	22.5 °	100	60	90	2	170	420						5		CABIN	20
490R	91-92		4.87	2.01	22.5 °	100	60	120		170	400						5		OPEN	20
492F	92-98		4.87	2.01	21-33 °	optional) 1C	60	90	2	170	420						5	500kg	CABIN	20
492L	92-99		4.87	2.01	21-33 °	100	60	90	2	170	420						5		CABIN	20
492R	92-96		4.87	2.01	21-33 °	optional) 1C	60	120	-		400						4		RUNABOUT	
492RF	92-00		4.87	2.00	21-33 °	optional) 1C	60	120		170	375						5		OPEN	20
500BR	05-10	5.05m	5.05m	2.10m	21-33 °	100	70	115		200	475	1120		6.10m	1.87m	2.10m	5	500kg	BOW RIDER	20
500RF	-11	5.05m	5.05m	2.10m	21-33 °	100	70	115	0	200	475	1120		6.10m	1.92m	2.10m	5 / 375kg	500kg	RUNABOUT	20
520BR	96-07	5.4	5.20	2.13	21-33 °	100	70	135	-	200	450						6	600kg	BOW RIDER	20
520R	96-07	5.4	5.20	2.13	21-33 °	100	70	135	-	200	450						6		OPEN	20
520RF	96-07			2.13	21-33 °	100	70										6			
530BR	-09	5.3	5.05m	2.20	21-33 °	100	75	140		200	475	1450		6.80m	1.88m	2.28m	6	600kg	BOW RIDER	20
530F	90-98		5.33	2.13	22.5 °	optional) 8:	75	125	2	200	560						5		CABIN	25
530L	90-98		5.30	2.13	22.5 °	optional) 1C	75	120	2	200	560						5		CABIN	20
530R	90-98		5.33	2.13	22.5 °	130	90	235		200	500						5		OPEN	20
532F	94-98		5.33	2.13	22.5 °	optional) 1C	75	125	2	200	560						5		CABIN	25
542CC	00-10	5.53m	5.33m	2.13m	21-33 °	100	90	150		240	550	1450		7.10m	2.60m	2.18m	7	700kg		25
542F	-08	5.53	5.33	2.13	21-33 °	96	100	140	2	240	600	1690	Optional 45L				7		CABIN	
542RF	1999	5.53m	5.33m	2.13m	21-33 °	100	90	150	0	240	550	1400		7.10m	2.17m	2.18m	7 / 525kg	700kg		25
550BR	90-96		5.33	2.03	21-29 °	165	75	140		200	560						5		BOW RIDER	20
550BR II	99-10	5.80m	5.50m	2.22m	21-33 °	150	100	150	2	240	600	1500		6.94m	1.80m	2.22m	7	700kg	BOW RIDER	25
550C	00-07		5.80	5.50	21-33 °	145	115	150	2	240	600	1690	Optional 45L	6.94	2.15	2.22	7	700	CABIN	25
550LE	90-96		5.33	2.03	21-29 °	165	75	125	2	200	610						5		CABIN	20
550R	00-06	5.8	5.50	2.22	21-33 °	145	115	150			550								RUNABOUT	
550RE	90-96		5.33	2.03	21-29 °	165	75	140	-	200	560						5		RUNABOUT	20
560BR	97-03	5.6	5.60	2.23	21-29 °	165	115	150	-	230	750						5		BOW RIDER	25
560C	97-03	5.6	5.60	2.23	21-29 °	165	90	150	2	230	750						5		CABIN	25
575F	95-06		5.85	2.35	21-33 °	185	115	150	2	230	820						5		CABIN	25

Model	Approx Year of Manufacture	Moulded Length with Bow Sprit	Length (m)	Beam (m)	Deadrise	Fuel O/B (L)	Min HP	Max HP	Berths	Max Eng Weight - Kg (O/B)	Approx Hull Weight (kg)	Approx Towing Weight (kg)	Water	BMT Length (approx)	BMT Height (approx)	BMT Width (approx)	Max People	Max load (people, gear, fuel)	Boat Type	Transom Height (inch)
600BR	92-95		5.95	2.21	22.5-34 °	165	90	200		230	650						6		BOW RIDER	20
600F Gen 1	92-94		5.94	2.20	22.5-34 °	165	90	150	2	230	780						6		CABIN	20
600F Gen 2	01-09	6.25m	5.95m	2.43m	21-33 °	150	115	175	2	240	850	1960	(optional) 45 l	7.54m	2.46m	2.43m	7	700kg	CABIN	25
600LE	90-96		6.56	2.44	22.5-34 °	165	90	150	2	230	800		Optional 50L				6		CABIN	20
600RE	90-96		5.94	2.21	22.5-34 °	165	90	200	-	230	650						6		RUNABOUT	20
602F	94-96		5.94	2.20	21-33 °	165	90	150	2	230	780						6		CABIN	25
610BR	97-05	6.45	6.10	2.41	21-33 °	165	135	225	-	270	800						6		BOW RIDER	25
610C	96-07	6.45	6.10	2.41	21-33 °	165	135	200	2	270	860						8		CABIN	25
630F	98-07	6.47	6.30	2.50	21-33 °	200	150	225	2	270	950	(OB) / 2200	Optional 45L				8		CABIN	25
630LE	90-96		6.25	2.28	22.5-31 °	210	115	200	2	270	750		Optional 50L				6		CABIN	20
630RE	90-96		6.25	2.28	22.5-31 °	210	115	200		270	700						6		RUNABOUT	20
650F	92-02		6.50	2.50	21-33 °	240	175	225	2	270	1000		Optional 30L				6		CABIN	25
660LE	90-96		6.56	2.44	22.5-31 °	210	135	200	2	270	800		Optional 50L				7		CABIN	20
660RE	90-96		6.56	2.44	22.5-31 °	210	135	200	2	270	800		Optional 50L				7		RUNABOUT	20
700L	90-95		6.86	2.50	22.5 °	220	150	225	2	270	950		64L				7		CABIN	20
700SB	90-95		6.86	2.50	22.5 °	270	175	220	4	270	1100		90L				7		SPORTSBRIDGE	20
702C	99-02	7.17	6.87	2.50	21-33 °	260	150	225	2	270	1100		Optional 90L				7		CABIN	25
702WA	99-02	7.17	6.86	2.50	21-33 °	236	150	225	2	270	1100		Optional 90L				7		CABIN	25
740RE	92-95		7.38	2.44	21-30 °	270	175	365	2	N/A	1100		Optional 45L				7		RUNABOUT	20
770C Twin C	04-10	8.42m	7.70m	2.69m	21-33 °	500			2 + 2	430	2200	na	200 l	na	na	na	8	800kg		25
850SB	89-95		8.54	3.00	21-30 °	various			4	N/A	3000		150L				8		SPORTSBRIDGE	NA